



PULVERISER **KL 115**

standard machine

- * chassis 6/10 mm steel with internal counter hooks
- * rotor Ø 180 mm tube with shaft ends Ø 50 mm
- * outside diameter flails Ø 440 mm
- * high rotor speed
- * automatic belt tensioner
- * heavy duty flail 2,2 kg with fixing bolt M20
- * gearbox 540 rpm
- * fix 3-point linkage cat II , Ø 28/25 mm
- * rear roller Ø 220 mm with double internal bearing
- * included drive shaft

- * pulveriser is equipped with double sweeper , hydraulic driven.
- * rotors of sweeper Ø 120 cm , each with 4 double rubberflaps , hydraulic width adjustable.

- * tractor needs to be equipped with the following hydraulic:

2x double acting valves for width adjustment of rotors (links and right independent)
1x single acting valve for running rotors
1x free return

different models available

art. nr.	type-model	cutting pulveriser cm	total working width max cm	flails #	V-belts #	gewicht kg	prijs €
160-015-160	KL160-115	165	360	10	4		
160-015-180	KL180-115	185	400	12	4		

options

1x	hydraulic - electric valve bloc with control box	on request
	in this case tractor needs :	1x single acting valve
		1x free return
		1x 12 volt plug

17-mei-21