

sprayer

QUATT

standard sprayer

- pump * diaphragmpump 140 liter COMET
- mixing * dust hydraulic mixer in basket
* injector with venturi
- wheel axle * single axle 60 mm with adjustable track
- wheels * tires 300/80-15,3 10 ply on rim 6 bolts
- fans * crossflow with 4x propellers ø 560 mm
2 speed gearbox with idle overdrive
height 340 cm with 2x 11 double nozzle holders
- nozzles * brass double nozzle bodies with Albus ATR nozzles
- filters * 1 suctionfilter, 50 mesh , easy to reach - adjusted to pump flow
* 2 high pressure filters, 50 or 80 mesh, in backside
- control * 2 sections with 2 elektrovalves , 27 watt with general switch
- pres, control * manuel
- pres, gauge * gauge 25 bar ø 100 mm class 1.0
- tank * polyethyleen or fibreglass tank from 1500 up to 2000 liter
* clean watertank to flush pump
* clean watertank for handwashing
- PTO-shaft * depending on drawbar
Weasler 2x double joint
or Bondioli single double joint
- drawbar * straight drawbar with fork
- general * metallized frame
* lights for road traffic
- pic: 1* 2000 liter polyethyleen
triprop 340 cm
tires 380/55-17



pic: 1



1500 liter smal
1500 liter
2000 liter

fibreglass
polyethleen
polyethleen

15-mei-21

QUATT

options

<u><i>pump</i></u>	* high-pressure , slow turning piston pump BAB 80 liter * brass diaphragmpump AR 135 litres	
<u><i>mixing</i></u>	* 2nd pump (centifugal) for mixing in tank , hydr. driven by tractor	
<u><i>wheel axle</i></u>	* double axle , fix under frame , with tires 10,0/75-15,3 14 ply * double axle , double swivel , with tires 10,0/75-15,3 14 ply * braked axle	per axle
<u><i>wheels</i></u>	* 380/55-17 12 ply flotation single axle * 340/50-16 12 ply flotation double axle	per pair
<u><i>drawbar</i></u>	* swivel hitch , heavy duty * ball coupling K80	 
<u><i>PTO-shaft</i></u>	* Walterscheid instead of Weasler WWZ 2380 double wide angle 80° lemon tube	
<u><i>nozzles</i></u>	* triple nozzle holders * drift reducing nozzles	a piece a piece
<u><i>pres. control</i></u>	* elektrical pressure regulation valve	
<u><i>control</i></u>	* 4 sections instead of 2 with 2 additional electrovalves	
<u><i>tower</i></u>	* height 370 cm with 2x 12 nozzles bodies	
<u><i>spraycomputer</i></u>	* Farmscan 74V1	price on request
<u><i>controller</i></u>	* Jack-all	price on request
<u><i>tank</i></u>	* 2000 litre fibreglass	