

sprayer

TURBLOW

standard sprayer

- pump diaphragmpump 140 liter COMET
- mixing * dust hydraulic mixer in basket
* injector with venturi
- wheel axle * single axle 60 mm with adjustable track
- wheels * tires 300/80-15,3 10 ply on rim 6 bolts
- fans * lower 1x propellor \varnothing 800 mm , with 12 adjustables blades
round design **pic 1 - 2**
2 speed gearbox with idle overdrive
- * upper 1x propellor \varnothing 800 mm , with 12 adjustable blades
round design **pic 1 - 2**
- nozzles * bottom 2x 6 brass double nozzle bodies with Albus ATR nozzles
* top 2x 5 brass double nozzle bodies
- filters * 1 suctionfilter, 50 mesh , easy to reach - adjusted to pump flow
* 2 high pressure filters, 50 or 80 mesh, in backside
- control * 4 sections with 4 elektrovalves , 27 watt
with general switch
- pres. control * manuel
- pres. gauge * gauge 25 bar \varnothing 100 mm class 1.0
- tank * polyethleen tank 1500 or 2000 liter
* clean watertank to flush pump
* clean watertank for handwashing
- PTO-shaft * depending on drawbar
Weasler 2x double joint
or Bondioli single double joint
- drawbar * straight drawbar with fork
- general * metallized frame
* lights for road traffic



pic:1



pic:2

pic 1 - 2: 1500 liter double axle - swivel hitch
fans housing standard 2x round design \varnothing 800/12

1500 liter narrow	fibre glass
1500 liter	polyethleen
2000 liter	polyethleen

15-mei-21

options

<u><i> pump </i></u>	* high-pressure , slow turning piston pump , BAB 80 l/min * brass diaphragmpump AR 135 l/min	
<u><i> mixing </i></u>	* 2nd pump (centifugal) for mixing in tank , hydr. driven by tractor	
<u><i> wheel axle </i></u>	* double axle , fix under frame , with tires 10,0/75-15,3 14 ply * double axle , double swivel , with tires 10,0/75-15,3 14 ply * hydraulically adjustable track width (only with fix axle) * braked axle	by axle
<u><i> wheels </i></u>	* 380/55-17 12 ply flotation single axle * 340/50-16 12 ply flotation double axle	by pair
<u><i> drawbar </i></u>	* swivel hitch , heavy duty * ball coupling K80	
<u><i> PTO-shaft </i></u>	Walterscheid instead of Weasler WWZ 2380 double wide angle 80° lemon tube	
<u><i> nozzles </i></u>	* triple brass nozzle bodies * drift reducing nozzels Albuz TVI	a piece a piece
<u><i> pres. Control </i></u>	* elektrical pressure regulation valve	
<u><i> fans housing </i></u>	* 2x propellor ø 800 mm with 16 blades instead of 12 blades * lower : crossflow with 2x 9 nozzle bodies * upper : air outlets directed downwards with 2x 6 nozzle bodies electrical adjustable air outlets with 2x 4 doppen	pic 3 - 4 pic 3 pic 3 pic 4
<u><i> sputcomputer </i></u>	* Farmscan 74V1	price on request
<u><i> controller </i></u>	* Jack-all	price on request

pic: 3



pic: 4